

Product features and benefits

Norcool has 30 years' experience of developing and producing cooling units. Today Norcool delivers compact cooling units, split units and cooling units for wine rooms. The cooling unit is placed in a recess/hole in the wall between the cold room and the tempered room where the warm part of the unit is placed. The cooling unit to be selected depends on the size of the cold room. Please contact your dealer or Norcool for further information.

Models

- Cooling Units:**
- ① Coolmaster CU-350 **Product number: 0512601710**
 - Coolmaster CU-450 **Product number: 0512602010**
 - Coolmaster CU-900 **Product number: 0514222010**
- Wine Refrigeration Units:**
- ② Coolmaster CU-350 Vin **Product number: 0512601810**
 - Coolmaster CU-450 Vin **Product number: 0512613010**
 - Coolmaster CU-900 Vin **Product number: 0514233010**
- Cooling Unit Split:**
- ③ Coolmaster CU-330 Split **Product number: 0512611710**
 - Coolmaster CU-450 Split **Product number: 0514212010**

Technical information

Cooling Units:	CU-350	CU-450	CU-900
Dimensions (mm)	W 505 x D 475 x H 535	W 590 x D 535 x H 690	W 590 x D 535 x H 690
Wall cut-out (mm)	W 460 x H 490	W 550 x H 650	W 550 x H 650
Capacity (litres)	> 5,000	> 10,000	> 20,000
Condensation	Automatic evaporation	Automatic evaporation	To drain
Thermostat setting	3-12°C	3-12°C	3-12°C
Ambient temperature	10-27°C	10-27°C	10-27°C
Requires ventilation	Yes, see user manual		

Wine Refrigeration Units:	CU-350 Wine	CU-450 Wine	CU-900 Wine
Dimensions (mm)	W 505 x D 475 x H 535	W 590 x D 535 x H 690	W 590 x D 535 x H 690
Wall cut-out (mm)	W 460 x H 490	W 550 x H 650	W 550 x H 650
Capacity (litres)	> 5,000	> 10,000	> 20,000
Condensation	Automatic evaporation	Automatic evaporation	To be drained
Thermostat setting	8-15°C	8-15°C	8-15°C
Ambient temperature	10-27°C	10-27°C	10-27°C
Requires ventilation	Yes, see user manual		

Cooling Unit Split:	CU-330 Split	CU-450 Split
Exterior dimensions warm part (mm)	W 440 x D 400 x H 290	W 620 x D 330 x H 690
Exterior dimensions cold part (mm)	W 550 x D 430 x H 145	W 590 x D 220 x H 385
Capacity (litres)	> 3,000	> 10,000
Condensation	To be drained	To be drained
Thermostat setting	3-10°C	3-10°C
Ambient temperature	10-27°C	10-27°C
Requires ventilation	Yes, see user manual	

NOTE! Split unit must be installed by an authorized refrigeration engineer.